


Albany


Albany is the latest addition to our advance tile technology collection, replicating the look of travertine without the ongoing maintenance or sealing. Albany has the flexibility to be used in both residential and commercial applications for both walls and floors. Available in 3 colourways, Cream, Grey and White and a range of sizes and finishes 300 x 300mm, 300 x 600mm, 450 x 450mm and 600 x 600mm matt finish and 450 x 450mm & 600 x 600mm textured finish with a P5 rating. Albany offers the complete solution where the look of Travertine is required.

ALBANY


COLOURS



Cream




Grey




White


FORMATS



600 x 600mm



450 x 450mm



300 x 600mm



300 x 300mm


FINISH: **MATT** CATEGORY: GLAZED FLOOR TILES | EDGE DETAIL: UNRECTIFIED | V RATING: V2

FINISH: **TEXTURED** CATEGORY: GLAZED FLOOR TILES | EDGE DETAIL: UNRECTIFIED | V RATING: V2







Cream




300 x 300mm
ALBCR30 (matt) P3



300 x 600mm
ALBCR36 (matt) P3



450 x 450mm
ALBCR45 (matt) P3
ALBCR45T (textured) P5



600 x 600mm
ALBCR60 (matt) P3
ALBCR60T (textured) P5




Grey




300 x 300mm
ALBGY30 (matt) P3



300 x 600mm
ALBGY36 (matt) P3




450 x 450mm
ALBGY45 (matt) P3
ALBGY45T (textured) P5



600 x 600mm
ALBGY60 (matt) P3
ALBGY60T (textured) P5


White




300 x 300mm
ALBWH30 (matt) P3



300 x 600mm
ALBWH36 (matt) P3



450 x 450mm
ALBWH45 (matt) P3
ALBWH45T (textured) P5



600 x 600mm
ALBWH60 (matt) P3
ALBWH60T (textured) P5



Technical Specification

	Properties	TestMethod	Required Value	Value	Applies to
	Water absorption	ISO 10545-3	$\leq 0.5\%$	$\leq 3\%$	All finishes
	Determination of dimensions	ISO 10545-2	Length and width $\pm 0.5\%$ Thickness $\pm 5.00\%$ Edge straightness $\pm 0.5\%$ Surface flatness $\pm 5\%$	Length and width 0.5% Thickness 5.0% Edge straightness 0.6% Surface flatness 0.5%	All finishes
	Breaking strength	ISO 10545-4	≥ 1300 N	2184 N	All finishes
	Abrasion resistance	ISO 10545-6	Class 3 min.	Complies with standards	All finishes
	Slip resistance (wet pendulum test)	Wet pendulum test	N/A	P3 – Matt P5 – Textured	Matt, textured
	Chemical resistance	ISO 10545-13	GB min.	Complies with standards	All finishes
	Stain resistance	ISO 10545-14	Class 3 min.	Complies with standards	All finishes
	Origin	N/A	N/A	Australia	All finishes
	Shade variation	N/A	N/A	V2	Full range

Packing Information

Tile description		Quantityper box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
300 x 300	Matt	22	11.11	14.05 kg	95.04	48
300 x 600	Matt	8	5.56	20.00 kg	69.12	48
450 x 450	Matt Textured	7	4.93	16.74 kg	113.60	80
600 x 600	Matt Textured	4	2.78	19.97 kg	69.12	48



The data and information contained in these specification sheets are indicative only unless stated otherwise.
As Japan Ceramics cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation.
The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose.
To the maximum extent permitted by law, Japan Ceramics will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.
No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

Slip Test Report – Batch Certification

National Ceramic Industries Australia Pty Ltd, ABN: 83 100 467 267

175 Racecourse Rd, Rutherford NSW 2320, Australia, Tel: +61 2 4931 8400 Fax: +61 2 4931 8499, www.ncia.com.au

Slip Resistance Classification of New Pedestrian Surfaces Materials Australia Standard AS 4586:2013 Appendix A (Wet Pendulum Test Method)

Production Year	2025	Test Sheet No:	Batch Test	Issue Date	27/08/2025	
Testing was conducted using a 96 rubber slider in accordance with the above Standard. Slider was prepared/conducted using P400C paper and 3 µm lapping film						
Code/s	Tile Name/s	Tile Size (cm)	Test Location	Cleaning Pre-testing	Results	Classification of Pedestrian Surfaces Materials according to the above Standard
ZAY1045A	Albany White	45X45	Tile Surface	Water & Scrubbing	Recorded	P3
ZAY2045A	Albany Grey	45X45	Tile Surface	Water & Scrubbing	Recorded	
ZAY3045A	Albany Cream	45X45	Tile Surface	Water & Scrubbing	Recorded	
ZAY1055A	Albany White	30X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY2055A	Albany Grey	30X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY3055A	Albany Cream	30X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY1060A	Albany White	60X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY2060A	Albany Grey	60X60	Tile Surface	Water & Scrubbing	Recorded	
ZAY3060A	Albany Cream	60X60	Tile Surface	Water & Scrubbing	Recorded	
Temperature (indoor)	20.8°C					
Testing Instrument	Pendulum Friction Tester, Calibration Date: 24 June 2024			National Ceramic Industries Australia Pty Ltd		
Reporting Officer	Hong Lu			NCIA Tiles Testing Laboratory		

Please note: Slip rating is indicative only. Actual performance may vary depending on installation, maintenance, cleaning, and environmental conditions. Customers should ensure suitability for their specific project requirements prior to installation.

ALBANY RANGE

White, Cream & Grey

NCIA Standard Slip Resistant Finish

BPN P5 slip resistance

300x600

Slip Resistant Finish P5 (Standard)



WET PENDULUM TEST

SLIP RESISTANCE REPORT

AS 4586-2013

CLASSIFICATION OF PEDESTRIAN SURFACE MATERIALS ACCORDING
TO
AS 4586 - 2013 WET PENDULUM TEST

Class	Slider 96 (4S)	Slider 55
P5	>54	>44
P4	45-54	40-44
P3	35-44	35-39
P2	25-34	20-34
P1	12 - 24	<20
P0	<12	

ncia
AUSTRALIA'S TILE MANUFACTURER

175 Racecourse Rd, Rutherford NSW 2320
PO Box 765 Maitland NSW 2320
Australia
Tel: +61 2 4931 8400 Fax: +61 2 4931 8499

Please note: Slip rating is indicative only. Actual performance may vary depending on installation, maintenance, cleaning, and environmental conditions. Customers should ensure suitability for their specific project requirements prior to installation.

ALBANY RANGE

White, Cream & Grey

NCIA Standard Slip Resistant Finish

BPN P5 slip resistance

450x450

Slip Resistant Finish P5 (Standard)



WET PENDULUM TEST

SLIP RESISTANCE REPORT

AS 4586-2013

CLASSIFICATION OF PEDESTRIAN SURFACE MATERIALS ACCORDING
TO
AS 4586 - 2013 WET PENDULUM TEST

Class	Slider 96 (4S)	Slider 55
P5	>54	>44
P4	45-54	40-44
P3	35-44	35-39
P2	25-34	20-34
P1	12 - 24	<20
P0	<12	

ncia
AUSTRALIA'S TILE MANUFACTURER

175 Racecourse Rd, Rutherford NSW 2320
PO Box 765 Maitland NSW 2320
Australia
Tel: +61 2 4931 8400 Fax: +61 2 4931 8499

Please note: Slip rating is indicative only. Actual performance may vary depending on installation, maintenance, cleaning, and environmental conditions. Customers should ensure suitability for their specific project requirements prior to installation.

ALBANY RANGE

White, Cream & Grey

NCIA Standard Slip Resistant Finish

BPN P5 slip resistance

600x600

Slip Resistant Finish P5 (Standard)



WET PENDULUM TEST

SLIP RESISTANCE REPORT

AS 4586-2013

CLASSIFICATION OF PEDESTRIAN SURFACE MATERIALS ACCORDING
TO
AS 4586 - 2013 WET PENDULUM TEST

Class	Slider 96 (4S)	Slider 55
P5	>54	>44
P4	45-54	40-44
P3	35-44	35-39
P2	25-34	20-34
P1	12 - 24	<20
P0	<12	

ncia
AUSTRALIA'S TILE MANUFACTURER

175 Racecourse Rd, Rutherford NSW 2320
PO Box 765 Maitland NSW 2320
Australia
Tel: +61 2 4931 8400 Fax: +61 2 4931 8499

Please note: Slip rating is indicative only. Actual performance may vary depending on installation, maintenance, cleaning, and environmental conditions. Customers should ensure suitability for their specific project requirements prior to installation.